

Stadium:	Tom/Objekt:	Teczka:	Branża:	Nr dokumentu:	Nr rewizji:	Strona/Stron:
PW	I	8.1	S	001	00	21 / 31

Nr osadnika	Objętość czynna - Vcz [m3]	Srednica wewnętrzna - D _w [mm]	Srednica zewnętrzna - D _z [mm]	Wysokość czynna - H _{cz} [mm]	Wysokość całkowita - H _c [mm]	Ciezar korpusu [t]	Srednica włazu	Ø [mm]	Srednica kolektora	D _z - DN [mm]
OP - I	5,0	2000	2300	1770	4100	~17,0	2x Ø600	600/500	600/500	600/500
OP - II	7,5	2500	2800	1700	4000	~17,0	2x Ø800	600/500	600/500	600/500
OP - III	7,5	2500	2800	1700	4000	17,0	2x Ø600	600/500	600/500	600/500
OP - IV	7,5	2000	2300	1290	3640	~11,0	Ø800/600	600/500	600/500	600/500
OP - V	5,0	2000	2300	1770	4100	13,0	Ø800/600	600/500	600/500	600/500
OP - VI	7,5	2500	2800	1700	4000	17,0	2x Ø600	600/500	600/500	600/500
OP - VII	7,5	2500	2800	1700	4000	~17,0	Ø800/600	600/500	600/500	600/500
OP - VIII	5,0	2000	2300	1770	4100	~13,0	Ø800/600	600/500	600/500	600/500
OP - IX	1,0	1200	1500	1050	2630	~4,0	Ø600	600/500	600/500	600/500
OP - X										

Tabela 1 Zestawienie parametrów osadników piasku - OP

Stadium:	Tom/Objekt:	Teczka:	Branża:	Nr dokumentu:	Nr rewizji:	Strona/Stron:
PW	I	8.1	S	001	00	23 / 31

Tabela 2. Zestawienie parametrów separatorów ropopochodnych - SO

Nr separatora	SO - I	SO - II	SO - III	SO - IV	SO - V	SO - VI	SO - VII	SO - VIII	SO - IX	SO - X*)
Przepustowość nominalna - Q1/Q2 [l/s]	40/400	40/400	40/400	40/400	20/200	40/400	40/400	40/400	30/300	6/60
Średnica wewnętrzna - Dw [mm]	1500	1500	1500	1500	1500	1500	1500	1500	1500	1200
Średnica zewnętrzna - Dz [mm]	1800	1800	1800	1800	1800	1800	1800	1800	1800	1440
Wysokość czynna - Hw [mm]	1670	1670	1670	1670	1670	1670	1670	1670	1670	1200
Wysokość całkowita - Hc [mm]	~4150	~4150	~4150	~4150	~4150	~4150	~4150	~4150	~4150	2800
Pojemność oleju - Vo [dm3]	460	460	460	460	460	460	460	460	370	136
Pojemność części osad. - Vos [dm3]	≥580	≥580	≥580	≥580	≥580	≥580	≥580	≥580	≥540	-
Ilość pak. larnelowych - n	2	2	2	2	1	2	2	2	2	1
Maks. średnica przył. DN [mm]	≤500	≤500	≤500	≤500	≤500	≤500	≤500	≤500	≤500	-
Średnica wężu Ø [mm]	wg Prod.	wg Prod.	wg Prod.	wg Prod.	wg Prod.	wg Prod.	wg Prod.	wg Prod.	wg Prod.	wg Prod.
Całkowity ciężar [t]	~10,0	~10,0	~10,0	~10,0	~10,0	~10,0	~10,0	~10,0	~10,0	3,4

*) układ nietypowy (fabrykat)